



Series	AGM-S	Warranty	See Warranty Terms
Volts	12	Design	22NF
Cells	6		
Terminal Type	F11(M6)		
Included Hardware	M6 stainless bolts & washers		
Size & Thread	M6		

Charge

Charge Voltage Range	14.7V @ 25°C (77°F)
Float Voltage Range	13.8V @ 25°C (77°F)
Recommended Charge Current	11 A
Maximum Charge Current	16 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)
Internal Resistance	7 mΩ

Capacity

Cold Crank Amps (CCA) 0°F / -18°C							360	
Hour Rate		Capacity / AMP Hour				Current / AMPs		
@ 20 Hour Rate		58 AH				2.9 A		
@ 10 Hour Rate		55 AH				5.5 A		
@ 5 Hour Rate		48 AH				9.6 A		
Cut Off Voltage		Constant Current Discharge						
1.75 VPC		1 hr	2 hr	3 hr	4 hr	5 hr	8 hr	10 hr
		30.55	18.11	14.2	11.26	9.61	6.7	5.57


Specifications

Weight	16.5 kg	36.5 lbs
Length	230 mm	9.05"
Width	138 mm	5.43"
Height Incl. Term.	215 mm	8.46"


Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Rope / Plastic Handle
- Plastics are UL94 HB (UL94 V0 available) - Valve regulated design with integral flame arrestor - Non-hazardous, Non-spillable	

Cycle Life vs. Depth of Discharge



Capacity vs. Temperature



Detailed Illustration

